



LETTERING - BLACK
 BACKGROUND - ORANGE
 HIGH INTENSITY
 REFLECTIVE
 SHEETING

BACK OF SIGN - OFF WHITE

NOTES:

1. **SIGNBOARD:**
 19mm THICK 1219mm x 2438mm DOUGLAS FIR PLYWOOD TO CSA-0121 STANDARD CONSTRUCTION MEDIUM DENSITY OVERLAY ONE SIDE.
2. SIGN FACE COATING TO BE HIGH INTENSITY GRADE REFLECTIVE SHEETING.
3. WEATHERTIGHT SEAL ON SIGNBOARD EDGES WOOD FILLER AND PAINT.
4. **TEXT INFORMATION:**
 SILKSCREEN OR ADHESIVE TYPE LETTERING MATERIALS WITH APPROVAL.
5. **PAINT:**
 THREE COAT ALKYD TYPE WITHOUT SILICONE ADDITIVES, 1st COAT: ALKYD PRIMER, 2nd & 3rd COATS: ALKYD GLOSS.
6. **COLOURS:**
 OFF-WHITE: GENERAL PAINT 4598W OR BENJAMIN MOORE 16-11.
 BLACK: ANY BLACK STANDARD.
7. **TYPOGRAPHY:**
 ALL TEXT - HELVETICA BOLD, UPPER CASE. "DEPARTMENT OF TRANSPORTATION" - HELVETICA LIGHT.



SD-200-02-52
 WARNING SIGN
 CONSTRUCTION
 Date: DEC 1995 Revised: MARCH 2002

Approved
Kehkeol
 Director
 Highways Division
 APR 21 2005
 Date